



4135

FLEET WASH INDUSTRIAL CLEANER DEGREASER

Environmentally Preferred
Specialty Cleaners



AEROGREEN 4135 INDUSTRIAL CLEANER DEGREASER was crafted by experts with over twenty years of experience and education in the development and technical support of environmentally preferred specialty cleaners. It attacks, quickly breaks down and safely removes dirt, exhaust soot, oils, greases, hydraulic fluids and fuel residue, as well as a variety of soils, leaving a residue clean surface.

AeroGreen 4135 helps companies meet their "Green Mandate" by providing a concentrated, water based, environmentally safe, industrial cleaner degreaser designed for use with both cold and heated high pressure washers. It can also be very effective when used as a pre-soak solution prior to steam cleaning.

It's time to stop using hazardous VOC solvents to clean and degrease your heavy machinery, industrial equipment and hard working vehicles. It's time to switch to a more user friendly, cost effective and 100% readily biodegradable industrial cleaner degreaser ... Solutions 4135.

CLEANES AND DEGREASES:

- Industrial equipment
- Trucks
- Machinery
- Engines
- Tankers
- Fleet vehicles
- Military vehicles
- Construction equipment
- Farm equipment

ADDITIONAL BENEFITS INCLUDE:

- A superior cleaner
- No odor
- Non-hazardous
- No hazardous waste
- Low VOC'S
- Non-combustible
- Requires no respirator or special hazardous training



AEROGREEN SOLUTIONS LLC
1285 Brucetown Road
P.O. Box 399
Clear Brook, VA 22624

www.AEROGREEN.US

P. 540.450.8375
F. 540.450.8379



4135

FLEET WASH INDUSTRIAL CLEANER DEGREASER

DIRECTIONS FOR USE AS PRE-SOAK CLEANER

- 1) Dilute: AeroGreen 4135 with water. 3:1 (3 parts water to one part Solutions 4135)
- 2) Add to Sprayer: Add the diluted cleaner degreaser to a coarse sprayer, or low-pressure sprayer.
- 3) Spray Area: Soak the entire surface to be cleaned to break down and emulsify the heavy oils, dirt, grease, hydraulic oils and greases from the surface that is being cleaned.
- 4) Soak time: After spraying, the parts shall be soaked effectively for a minimum of 10-15 minutes prior to using steam to clean the surface.

DIRECTIONS FOR HOT OR COLD PRESSURE WASHERS

- 1) Wet: Wet surface to be cleaned with water
- 2) Apply: AeroGreen 4135 based on equipment PSI (see dilutions chart). Follow equipment manufacturer's directions for equipment use.
- 3) Rinse: Rinse cleaned surface with water.
- 4) Rust-Preventative: For items that have a tendency to rust or if specification requires, use approved rust inhibitor after cleaning.

DILUTIONS

Aero-Green 4135 can be used with both cold and heated old pressure washers are based on the PSI of the equipment being used:

PSI	WATER:CLEANER
100-500.....	8:1
500-1000.....	10:1
1000-2000.....	15:1
2000-3000.....	25:1
3500-Plus.....	30:1

SPECIFICATIONS

Biodegradability	Yes
Flammable	No
Combustible	No
SCAQMD	Yes
Water Solubility	100%
Contains Terpenes	No
Caustics	No
Oil/Water Separator and/or	
Pre-treatment Compatibly	

USING A FOAM GENERATOR:


For large equipment use a Foam Generator machine to get at hard to reach areas. Set the machine to lay a thick blanket of solution on the surface to be cleaned to dissolve and remove heavy oils, grease, dirt, and hydraulic fluids from the surface that is being cleaned.

- 1) Dilute: Set the foam unit at dilution of 8:1 (8 parts water to one part AeroGreen 4135)
- 2) Spray: Spray an even layer of foam over the section to be cleaned. Apply from the bottom to the top to minimize streaking.
- 3) Soak: Allow to soak for 2-3 minutes.
- 4) Rinse: With a pressure washer rinse to remove all dissolved soils

SAFETY/CAUTION

Rubber gloves are recommended to prevent drying of the skin. Goggles are recommended to protect eyes if splashing is expected. When heated above 125 F, mechanical or local ventilation is required. When using product in steam cleaning and/or pressure washing applications wear a rain suit and boots to keep clothes dry.

Harmful if swallowed. Avoid getting into eyes. If contact occurs, flush with running water. If irritation persists get medical attention. May cause dryness of skin with prolonged use, wash hands with cold water and apply a hand lotion.



Directions for use in **Español** and **Français** available online at:

www.aerogreen.us/instructions

© 2011 Hi-Lite Solutions, Inc. All Rights Reserved.