Donaldson.

WELD BENCH FUME COLLECTOR

MODELS WB-2000 AND WB-3000







Work bench designed specifically for welding operations.

- Eliminates moving extraction arms over the welding zone
- Meets ACGIH guidelines for capturing weld fume—150 fpm minimum capture velocity through the breathing zone
- Provides a cleaner work environment for maximum productivity
- Hinged side-wing panels accommodate longer workpieces
- Ergonomically designed for operator comfort

- Easy filter maintenance from clean air side makes filter changeout quick and efficient
- Standard Ultra-Web® FR cartridges, with fine fiber technology, provide higher filtration efficiency and longer filter life
- MERV* 15 filtration efficiency rating per ASHRAE 52.2-2007
- Helps support OSHA Clean Air Standards
- Quiet operation

DIMENSIONS & SPECIFICATIONS





Model	Nominal Airflow**		Motor (hp)	Backdraft		Dimensions								Dust		Max Load		Shipping		Sound		
					m/		Α		В		C		D		E		Capacity		per sq. ft.		eight	Level
	cfm	m³/h	(IIP)	fpm	min	in	mm	in	mm	in	mm	in	mm	in	mm	ft³	m³	lb	kg	lb	kg	dB(A)
WB-2000	2000	3397	3	150	45.7	42.0	1066.8	52.0	1320.8	38.0	965.2	52.0	1320.8	75.0	1905.0	1.4	0.04	150	68.0	1214	550.7	68
WB-3000	3000	5096	5	150	45.7	42.0	1066.8	52.0	1320.8	38.0	965.2	78.0	1981.2	75.0	1905.0	2.8	0.08	150	68.0	1575	714.4	72

Note: Customer must have 90 to 100 psi clean air available.

STANDARD FEATURES & AVAILABLE OPTIONS

STANDARD	OPTIONAL						
7-gauge heavy-duty work surface supports 150 lbs/ft² (732.4 kg/m²)	Prewired controls with after-shift cleaning system						
Automatic self-cleaning pulse jet system	IEC disconnect						
150 fpm (45.7 m/min) backdraft velocity	Fluorescent Light						
Quiet, efficient airfoil fan	* The Minimum Efficiency Reporting Value (MERV) of this filter cartridge has been determined through independent laboratory testing using ASHRAE 52.2 (2007) test standards. The MERV rating was determined at a face velocity of 118 feet per minute (36.0 meters per minute) and loading up to four inches (101.6 millimeters) water gauge. Actual efficiency of any filter cartridge will vary according to the specific application parameters. Dust concentration, airflow, particle characteristics, and pulse cleaning methods all affect filtration efficiency. ** Based on clean filters.						
Large capacity dust drawers							
Ultra-Web® FR cartridge							
Pneumatic tool connection	† Sound level per ANSI \$12.34.1988. The actual measured sound level will vary, depending on background noise and room conditions.						
Sprinkler head	Significantly improve the performance of your collector with genuine Donaldson Torit replacement filters and parts. Call Donaldson Torit at 800-365-1331.						
10-year warranty							

Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Donaldson Company, Inc. Minneapolis, MN

donaldsontorit.com • shop.donaldson.com

North America

Email: donaldsontorit@donaldson.com Phone: (USA): +1-800-365-1331 • (MX): +1-800-343-36-39

Australasia

Email: marketing.australia@donaldson.com Phone: +61-2-4350-2000

Toll Free: (AU) +1800-345-837 • (NZ) +0800-743-387 Phone: +81-42-540-4112 F118171 ENG (03/20) Weld Bench Fume Collector WB-2000 and WB-3000 ©2011-2020 Donaldson Company, Inc.

Donaldson, Torit, Ultra-Web and the color blue are marks of Donaldson Company, Inc. All other marks belong to their respective owners.

China

Email: info.cn@donaldson.com Phone: +86-400-820-1038

Donaldson Europe B.V.B.A. Email: IAF-europe@donaldson.com

Phone: +32-16-38-3811

Email: info.difs@donaldson.com Phone: +91-124-4807-400 • +18001035018

Email: jp-ndl.ifsweb@donaldson.com

Email: iaf-kr@donaldson.com Phone: +82-2-517-3333

Latinoamerica

Email: IndustrialAir@donaldson.com Phone: +52-449-300-2442

South Africa

Email: SAMarketing@donaldson.com Phone: +27-11-997-6000

Southeast Asia Email: IAF.SEA@donaldson.com Phone: +65-6311-7373