

BNP 6012 and 7212 Pressure Blast Cabinets



Clean Peen Deburr Finish



with CDC For tough cleaning jobs, pressure blasting delivers higher abrasive velocity for greater impact intensity, compared to suction blasting, and can increase your production rate by as much as 300 percent.

New- bolt-on sump pipes and pipe adaptors, and dimensional changes that affect curtain sizes. **CAUTION:** Curtain sizes differ; take care

when ordering replacement curtains or alox kits for older 600 and 720 models.

Common **Applications**

- Remove rust, mill scale, heat scale, and carbon buildup from metals
- Strip paint, powder coating, plating, and anodizing from parts for rework
- · Eliminate burrs, parting lines, flashings, and other defects from castings and injection-molded parts
- · Extract residual sand from castings
- Beautify steel, stainless steel, aluminum, brass and other metals with a uniform matte finish
- Etch artwork and lettering into glass, stone, plastics, metal and other materials
- Clean release agents and material buildup from molds

BNP 6012/7212 Pressure Cabinets Feature: Safety

- ✓ Full-length, neoprene-on-fabric gloves resist wear and protect operator.
- ✔ Ceiling-mounted, four-tube fluorescent light fixture with abrasive resistant wire-embedded glass cover for extraordinary visibility.
- ✓ Safety interlocks interrupt blasting if either door is opened.
- ✓ Heavy-duty, cam-style latch seals doors tight through years of service.

Productivity

- ✓ High efficiency, 2.0 cubic foot capacity, ASMEcoded pressure vessel, fitted with 1" ID piping, industrial-quality blast hose and couplings and cabinet integrated controls.
- ✓ Unique Air-Logic system (pilot-actuated) to maximize air flow to the nozzle.
- ✓ Double-wall, sound-insulated door sET.
- ✓ 12-gauge steel all-welded construction, with strength breaks to form a rigid, long-lasting cabinet shell.
- ✓ Large 20" x 30" view window.

Convenience

- ✓ Tilt-out window, for tool-free glass changes in minutes.
- ✓ Pressure regulator, gauge, and electric switch mounted within easy reach.
- ✔ Built-in blow-off gun helps keep dust inside the cabinet, not on your floor.
- ✓ Bolt-on sump pipes allow easy replacement for maintenance.

Tungsten Carbide Blast Nozzle

The standard No 3 tungsten carbide nozzle is perfect for most blasting, while the optional boron carbide nozzles stand up to hundreds of hours of blasting with aluminum oxide or other aggressive abrasives.


Popular Accessories

- Air-powered vertical lift door
- Alox kit (for harsh media)
- Armrest assembly
- Curtains (black or white)
- HEPA filter
- · Manometer kit
- Timed door release
- 30", 40, and 48" dia. turntables • with or without work car and 9 ft track extension
- · Additional operator station
- Additional door set
- · Door set moved to opposite side

S Ρ F С S E С Δ Ν Ο

COMPLETE SYSTEM

Space required depends on configurations, options and work flow. Allow space for operator and maintenance access. See maintenance access height (MAH) below



CDC-1 dust collectors come in three sizes; 300 cfm, 600 cfm, and 900 cfm. The cartridges are pulse-cleaned by pressing the manual pulse valve to clear the filter of dust. Dimensions are 34" wide, 42" deep (with motor housing) and 94" high. The MAH is 11 ft for the 300 and 600 cfm units and 12-1/2 ft for the 900 cfm unit.

RPC-2

The RPC-2 has two cartridges which provide 470 sq ft of filter area. The cartridges are automatically pulse cleaned for maximum filter efficiency. Dimensions are: 56" wide by 36" deep by 67.5" high. The MAH for the RPC-2 series is 8 ft 10 inches.

RPH-2 and RPH-3

The RPH-2 has a filter area of 470 sq ft; the RPH-3 has 705 sq ft filter area. Both have a built-in hopper to minimize dust handling. At each pulse, dust falls first into the hopper and then into a disposal drum or bag beneath it. The operator never handles the dust - an important safety feature. RPH-2 dimensions are: 56' wide (with motor housing) by 36" deep by 115" high. The RPH-3 is: 91" wide (with motor housing) by 48" deep by 143" high. The RPH is designed to allow outdoor installation. The MAH for the RPH collectors is 15 ft 2 inch.

ISO 9001 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.


BLAST/ RECLAIM SYSTEM

The Heart of ZERO's Blasting System

Our exclusive media reclaimers continuously extract dust and debris and return properly sized, usable media to the blast system. The standard reclaimer handles all non-metallic media. For metallic media, choose from the two PM models.

The reclaimer. mounted atop the pressure vessel, automatically re- Reuseable media fills the blast system with clean, recycled media.

The versatile design of our larger reclaimers lets you quickly adapt the system to your changing needs.



NOZZLES

AIR REQUIREMENTS

NOZZLE			M³/Min at 5,5 BAR		M³/Min at 7 BAR				
No. 3	3/16"	38	1,08	45	1,3				

BNP 6012P and BNP 7212P come with a No. 3, 3/16" orifice, tungsten carbide nozzle

ELECTRICAL

900 CFM (25 m³/m) 2HP, 3PH, 60HZ, (1.5KW, 220V, 3PH, 50HZ,); 1200 CFM (34 m³/m) 5HP, 3PH, 60HZ, (3.7KW, 220V, 1PH, 50HZ,); available with three phase motors only.

ORDERING INFORMATION

Model Number	Reclaim CFM (m ³ /m)	Dust Coll.	230V Stock No.	460V Stock No	Ship Wt. b. lb(kg)
Note: 1200 cfm reclai	m or larger is	required	for metallic	media	
BNP-6012P-900 CDC	C 900 (25)	CDC-1	28394	28395	2569 (1165)
BNP-6012P-900 RPC	900 (25)	RPC-2	25481	25482	2,849 (1292)
BNP-6012P-900 RPH	1 900 (25)	RPH-2	25485	25486	3,424 (1553)
BNP-6012P-1200 RPH	1200 (34)	RPH-3	25489	25490	4,115 (1867)
BNP-7212P-900 CDC	C 900 (25)	CDC-1	28398	28399	3,125 (1417)
BNP-7212P-900 RPC	900 (25)	RPC-2	25507	25508	3,405 (1544)
BNP-7212P-900 RPH	1 900 (25)	RPH-2	25511	25512	3,980 (1805)
BNP-7212P-1200 RPH	1200 (34)	RPH-3	25515	25516	5,025 (2279)
	Metali	c Media M	Iodels		
BNP-6012PM-1200 RI	PH 1200 (34)	RPH-3	27460	27461	4,115 (1867)
BNP-7212PM-1200 RI	PH 1200 (34)	RPH-3	27462	27463	5.025 (2279)

Stock No.: 20011

© 2016 Clemco Industries Corp. • Washington, MO 63090 • 636 239-0300 • FAX 800 726-7559 info@clemcoindustries.com • www.clemcoindustries.corp