



AEROGREEN 4130 HIGH PRESSURE (WAND CLEANING) CLEANER-DEGREASER

The use of **Aerogreen 4130 High-Pressure Cleaner-Degreaser** will help clean and degrease large parts and equipment in a short amount of time using power washing equipment. Whether to clean for repairs, inspection or repainting, **Aerogreen 4130** will safely insure the job gets done efficiently.

Aerogreen 4130 High Pressure Cleaner-Degreaser used as a Paint-Prep is the best product for cleaning the surface prior to painting by removing soils that cause adhesion issues with coatings due to contaminants on the surface.



Before coating

Aerogreen 4130 can be used as a cleaner prior to inspection and repairs for equipment by removing the oils, dirt, grease, waxes, polishing compounds, salts, soluble oils, drilling and cutting compounds from the surface.

Aerogreen 4130 can be safely used in between primer and top coat and as a final cleaning for preparation to ship.

Aerogreen 4130 meets the standards as listed under SSPC-SP1.

Aerogreen 4130 is developed specifically for use to clean surfaces prior to painting and will not leave a soapy residue behind that interfere with coating adhesion.



Before coating

COMPATIBILITY:

Aerogreen 4130 is compatible with: Lacquers, Acrylic Enamels, Fast Drying Coatings, Solvent Based Coatings, Water Based Finishes / Primers, Metal Finishes, Polyurethanes, Sealers, Clear Coats, Powder Coatings, Military Coatings, Water Reducible Finishes & Primers, Epoxy Finishes, Acrylic Latex, Plastic Finishes, Pigmented Topcoats.



Before Sand Blasting



Exterior Building Surfaces



Technical Information

Aerogreen Product Number

4130P- 5- Gallon Pail
4130D-55- Gallon Drum
4130T275-275 Gallon Tote
4130T330-330 Gallon Tote

Product Information:

Aerogreen 4130 High Pressure Cleaner -Degreaser is manufactured to clean and degrease equipment and parts fast and efficiently. Whether a hot or cold water is used through the power washing equipment, **Aerogreen 4130** will safely remove all dirt, grease and oils. The product contains no VOC's and is safe for disposal through the normal water system.

Features:

Concentrated solution
Dilution range from 3:1 to
1:1 Low VOC's
Leave no residue

Benefits:

Easy to mix and fast to use
Light to heavy dirt-soils-oils are removed
Safe for the environment
Labor savings

Application Guidelines:

Use as a pre-soak: Dilute **Aerogreen 4130** 3:1 with water (3 parts water to 1 part 4130). Spray using a pump sprayer the area to be cleaned. Let soak for 1-3 minutes. Rinse using a pressure washer (1,000-3,000 psi). Dry with either an air hose or clean cloth prior to painting.

Use with a pressure washing system: Wet the surface to be cleaned with water. Set the dilutions jets at 10%. Drop feeder hose into **Aerogreen 4130** solution to draw into the pressure washer. Clean the area and then dry with air or using a clean cloth.

Specifications:

Flammable Combustible	NO
Water Solubility	100%
Contains Terpenes	NO
SCAQMD Certified	YES
lbs/glpH @ Concentrate	12.0-12.3
pH @ 3:1 Dilution	10.0-11.0
Density lbs. /per gal	8.9 lbs/gl
VOC- SCAQMD Method 313.91 Concentrate	47 g/l
VOC-SAQMD Method 313.91 diluted 2:1	15 g/l
100% Readily Biodegradable 313.91	Yes

SAFETY/CAUTION:

Rubber gloves are recommended to prevent drying of the skin. Goggles are recommended to protect eyes if splashing is expected. When heated above 125 F, mechanical or local ventilation is required. When using product in steam cleaning and/or pressure washing application wear a rain suit and boots to keep clothes dry. Harmful if swallowed. Avoid getting into eyes. If contact occurs, flush with running water. If irritation persists, get medical attention. May cause dryness of skin with prolonged use, wash hands with cold water and apply a hand lotion.