

# **AEROGREEN 4135 FLEET WASH INDUSTRIAL CLEANER DEGREASER**

<u>AEROGREEN 4135 Fleet Wash Industrial Cleaner Degreaser</u> was developed by a chemist to quickly attack and break down dirt, exhaust soot, oils, greases, hydraulic fluids and fuel residue, as well as a variety of soils, leaving a residue- free, clean surface.

<u>Aerogreen 4135</u> helps companies meet their "Green mandate" by providing a concentrated, water based, environmentally safe, industrial cleaner degreaser designed for use with both cold and heated high pressure washers. It can also be very effective when used as a pre-soak solution prior to steam cleaning.

It's time to stop using hazardous VOC solvents to clean and degrease your heavy machinery, industrial equipment and hard working vehicles. It's time to switch to a more user friendly, cost effective and 100% readily biodegradable industrial cleaner degreaser - <u>Aerogreen 4135</u>.

### Cleans and Degreases:

- Industrial equipment
- Trucks
- Machinery
- Engines
- Tankers
- Fleet vehicles
- Military vehicles
- Construction equipment
- Farm equipment



Construction Equipment-Farm Equipment-Roadway Equipment



Use with Foam-It to Clean with Blanket of Foam and Rinse with Pressure Washer









### **Technical Information**

#### Aerogreen Product Number

4135P- 5- Gallon Pail 4135D-55- Gallon Drum 4135T275- 275 Gallon Tote 4135T330-330 Gallon Tote

## AEROGREEN 4135 FLEET WASH INDUSTRIAL CLEANER-DEGREASER

### **Product Description:**

Aerogreen 4135 Fleet Wash Industrial Cleaner Degreaser is made to clean many different types of autos, trucks and equipment fleets, including military, using environmentally safe materials.

### **Application Guidelines:**

<u>Use as a pre-soak cleaner</u>: Dilute <u>Aerogreen 4135</u> 3:1 (3 parts water to 1 part 4135). Add to pump or low pressure sprayer. Spray the entire area to be cleaned and let soak for 10-15 minutes depending upon the level of dirt and grime. Rinse entire the surface with water using hose or power washer.

Use of Power Washer to clean: Wet the entire surface to be cleaned. Apply Aerogreen 4135 based on dilution chart:

PSI:	Dilution (water to Aerogreen)
100-500	8:1
500-1000	10:1
1000-2000	15:1
2000-3000	20-1
3000+	25-1

Rinse with power washer and let dry. Apply Aerogreen AC-10 as a 2% solution to areas that are prone to rusting.

### **Specifications:**

Readily Biodegradable	Yes
Flammable	No
Combustible	No
SCAQMD Certified	Yes
Water Solubility	100%
Contains Terpenes	No
Caustics	No
Oil/Water separator compatible	Yes
Density Lbs/Gal	8.6 Lbs/Gal
pH Concentrate	12.0-12.3
pH 3:1 Dilution	11.0-11.5
Color/Characteristic	Green/Liquid
Concentrate	Yes

### **SAFETY/CAUTION:**

Rubber gloves are recommended to prevent drying of the skin. Wear goggles to protect eyes if splashing is expected. When heated above 125 F, mechanical or local ventilation is required. When using product in steam cleaning and/or pressure washing applications wear a rain suit and boots to keep clothes dry.

Harmful if swallowed. Avoid getting into eyes. If contact occurs, flush with running water.

If irritation persists get medical attention. May cause dryness of skin with prolonged use, wash hands with cold water and apply a hand lotion.