

# LB-160i Finishing Compound



LB-160i is a ultra low foaming neutral pH, recyclable, liquid finishing compound formulated specifically for use in high energy equipment including drag finishing and centrifugal disk and centrifugal barrel machines. Effluent will be low foaming even with plastic media. It is biodegradable and does not contain any hazardous ingredients. This product is formulated for use on all ferrous metals and most nonferrous alloys. LB-160i works well under a wide range of conditions and can withstand moderate soil loads. Unique dispersion characteristics allow for fast surface improvement while attaining excellent color and reflective qualities.

## PHYSICAL PROPERTIES

Appearance	Yellow Liquid
pH @ 1% solution	9.3
Odor	Mild
Foaming Action	Low
Solubility in Water	Complete
Rinsing Action	Excellent
Metal Safety	All Metals
Flash Point	None
Specific Gravity	1.03
Stability	Stable
Standard Container	55 gallon drum

*Refer to our Material Safety Data Sheet for additional information.*

## USAGE AND DILUTION RECOMMENDATIONS

Use 1 to 3 ounces per gallon of water. Water flow will vary depending on media, parts, cut-down times, etc.

## HANDLING AND STORAGE

LB-160i Finishing Compound is a neutral pH product and does not pose any fire hazards. It may cause eye irritation upon contact. Prolonged or repeated skin contact may be drying to sensitive skin. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, and other appropriate protective measures. Do Not Freeze! Store product in tightly closed containers between 50° and 85° F. Rotate stock. When stored as stated above, shelf life is a minimum of 2 years

*Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 65 years experience. Our quality management system has been certified to ISO 9001 Quality Standards.*