# LB-892

## **Finishing Compound**



LB-892 is a mildly acidic, burnishing compound for use on ferrous and most non-ferrous metals. An excellent burnishing compound with good lubricity, controllable foam and light cleaning ability. LB-892 yields exceptionally high color and luster in ball burnishing operations. When used with steel media in burnishing operations, the media obtains and retains maximum brightness. While primarily a steel media burnishing compound, LB-892 can also be used with ceramic and natural media. Steel media and parts should be inhibited to prevent corrosion.

### **USAGE & DILUTION INSTRUCTIONS**

For most conditions use 3/4 to 2 ounce per gallon of water. Water flow rate for most situations should be 2 gallons per hour per cubic foot of mass in the machine. For example a 20cubic foot vibratory machine should require a flow rate of 40 gallons per hour. Inhibit media with our 50-R or PR-100 corrosion inhibitors.

#### PHYSICAL PROPERTIES

Appearance Blue liquid

pH @ 1% solution 4.6 Mild

Odor

Controlled Foaming action

Solubility in water Complete

Excellent Rinsing action

**Metal Safety** Ferrous & Non-

> ferrous None

1.04

Stable

Flash point

**Specific Gravity** 

Stability

Standard Container(s) 55 Gallon Drum

### HANDLING AND STORAGE **INSTRUCTIONS**

Product does not pose any fire hazards. This moderately acidic product should be stored in original containers or similar plastic containers that are properly labeled. In case of skin contact, wash with soap and water. In case of eve contact, flush with plenty of water for at least 15 minutes and call physician. recommended that eye protection and rubber gloves be worn as product may irritate sensitive skin. Follow good industrial hygiene practices. Do not freeze. Store product in tightly closed containers between 50° and 85° F. Rotate stock. When stored as stated above, shelf life is a minimum of 2 years.

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 60 years experience. Our company has been certified to ISO 9001:2000 Quality Standards.

Refer to our Material Safety Data Sheet for additional information.

Rev. 1/09

