



Consumables




Mass Finishing



High-performance equipment and innovative technologies – productive and cost-effective

Shot Blasting



Customer-oriented equipment technology and intelligent process solutions – long-lasting and energy-efficient

AM Solutions



Comprehensive solutions for additive manufacturing, especially 3D post processing equipment

>80

More than 80 years of **experience**




15 locations –
over **150** distributors –
over **1,500** employees **across the globe**



Worldwide **Customer Experience Center**



More than **15,000**
different types of media and compounds



Our technical service –
round-the-clock support



Transfer of professional knowledge
by certified trainers

Contents

Consumables	4
Customer Experience Center Mass Finishing	5
Selection criteria for Rösler consumables	6 - 7
Media and compound production	8 - 9
Ceramic media	10 - 13
Plastic media	14 - 15
Mass finishing compounds	16
Compounds for process water recycling systems	17
Compounds for applications using fresh water	18
Powder compounds	19
Grinding pastes and grinding powder	20
Polishing pastes and polishing powder	21
Dry polishing	22
Auxiliary mass finishing media	23
Process water cleaning	24 - 26
Rösler Smart Solutions	27

MEDIA AND COMPOUNDS

In addition to our equipment portfolio we can also offer the worldwide most comprehensive range of media and compounds, these are developed and produced in-house with the highest "made in Germany" quality. With more than 80


years of experience in the field of surface treatment we not only supply individual solutions for new finishing applications but also assist our customers to exploit the potential for product improvement and cost savings.

Developing stable processes with repeatable results is our business



The worldwide most comprehensive range of media and compounds in the market

With 15,000 individual products our consumables portfolio is by far the most comprehensive in the world. It includes ceramic and plastic grinding and polishing media, compounds and process water cleaning agents. Because of their excellent quality many of our consumables are approved for use in the aerospace, medical engineering and automotive industry. Of course, they can always be adapted to the requirements of our customers.



Our ceramic media production

Excellent quality and quick availability

We produce in compliance with strict ecological standards and our consumables production is subject to strict quality controls per DIN EN ISO 9001.

In our central warehouse we stock a minimum of 8,000 tons of media and compounds at any time. This allows us to quickly supply our customers around the world with the consumables they need.

CUSTOMER EXPERIENCE CENTER

MASS FINISHING

A major strength of the Rösler business approach is that **we look at all aspects of a finishing task**. The equipment and the processes are individually tailored to the respective finishing requirements, but also to their optimal integration into the customer's manufacturing operation. Most of the Rösler sales

branches have their own **Customer Experience Centers (CEC)**, equipped with the latest finishing equipment.

To investigate the various finishing possibilities, in our CEC we are conducting **processing trials** with the work pieces of our respective customers.



Process development and process optimization

Our all-around approach guarantees perfect finishing solutions. This includes processing trials, process development, selection of the right machinery and a professional after sales service.

In our CEC, equipped with ultra-modern equipment, we can run practically any mass finishing process.

State-of-the-art **physical and chemical measuring** equipment represents a vital tool for process development and optimization.

The entire focus of our specialists in the engineering and R & D departments is on developing **tailormade finishing solutions**.

Product development and optimization

The enormous depth of the Rösler product range, CEC around the world and our well-equipped laboratory at the Untermerzbach location in Germany are an excellent basis for the development of innovative and cost-efficient products in the field of mass finishing.

All our products, be it consumables, finishing equipment,

vibratory motors, process water cleaning centrifuges, as well as work piece handling systems and post processing equipment like dryers, are **developed and manufactured** in-house. Such a high manufacturing depth is unparalleled in our industry.

SELECTION CRITERIA FOR RÖSLER CONSUMABLES

Mass finishing processes

Deburring | Cut-down (rough grinding) | Fine grinding | Surface smoothing | Brightening | Polishing | Edge radiusing | Cleaning | Degreasing/De-oiling | Descaling | De-rusting | Corrosion protection | Ball burnishing | Pressure deburring

Media	Type	The grinding performance and the surface finish depend on which media type is selected.
	Shape	To reach all surface areas on the work pieces the shape of the media must be adapted to the work piece geometry. This also helps prevent media lodging in the work pieces. The media shape also affects the grinding performance: Round and curved shapes are generally less aggressive than media with edges.
	Size	Larger and heavier media produce a more intensive grinding performance but create a rougher surface finish.
	Separation	There must be a sufficiently big size difference between work pieces and media to allow safe separation of the finished work pieces from the media. Ferromagnetic work pieces can be separated from the media with magnetic tools. For special applications we develop individual separation solutions.
Compounds	Type	<p>The purpose of mass finishing compounds is primarily to keep the surface of the media and work pieces clean and to make sure that the mass finishing processes remain stable.</p> <p>The compound selection usually depends on</p> <ul style="list-style-type: none"> ▶ The work piece material ▶ The finishing application ▶ The desired compound characteristics ▶ The finishing objective
Additives	Defoamers	For the quick suppression of unwanted foam in the finishing machine we offer various defoamers. The commonly used products are our additives ES3, ES4 and ES7. Our defoamers are easy to handle. They can be directly sprayed into the machine or added to the process water.
	Corrosion protection and increased degreasing effect	For boosting the desired finishing effect we offer various additives. These are generally in liquid form and can be added batchwise or continuously.
	Biocides	Biocides are frequently used in process water recycling systems. They reduce the risk of bacterial infection and facilitate maintenance of the process water. This results in higher uptimes and fewer changes of the process water.

If you have any questions, please contact us or our sales representatives.

Special processes

<p>RÖSLER Keramo-Finish®</p>	<p>The RÖSLER Keramo-Finish® process is ideal for polishing work pieces made from iron, iron alloys, steel, stainless steel, brass, copper, silver and certain zinc alloys.</p> <p>The respective media and compounds are</p> <ul style="list-style-type: none"> ▶ RP and RCP porcelain media with minimal wear for surface grinding and polishing operations ▶ RÖSLER Keramo-Finish® pastes, type RSP and RPP ▶ Rösler compounds, type FC and ZF, for rinsing out the paste, surface cleaning, corrosion protection, brightening and high gloss polishing
<p>Rösler ISF</p> <p>Chemically accelerated mass finishing</p>	<p>The ISF (isotropic finishing) method combines chemical and mechanical surface treatment effects. It is ideal for finishing the surface of high-value components without rounding the work piece edge.</p> <p>The respective media and compounds are</p> <ul style="list-style-type: none"> ▶ Special ISF media, type FM ▶ Compounds for chemically accelerated mass finishing. The compounds are specially adapted to the respective work piece materials.
<p>Rösler ball burnishing and pressure deburring</p>	<p>Ball burnishing is a cost-efficient process that generates a decorative luster on work pieces made from steel, stainless steel and non-ferrous metals. At the same time it has a light deburring effect and breaks sharp edges.</p> <p>The respective media and compounds are</p> <ul style="list-style-type: none"> ▶ Carbon steel and stainless steel media, type RESK, RESA or SAT, for ball burnishing and pressure deburring. There is practically no media wear. ▶ Ball burnishing compounds, type FC. The compounds are frequently adapted to special finishing applications.
<p>Rösler dry polishing</p>	<p>Granular polishing media create extremely fine surface finishes. They cause minimal material removal from the work pieces and produce very smooth, shiny surfaces, as if polished by hand.</p> <p>The respective media and compounds are</p> <ul style="list-style-type: none"> ▶ Rösler polishing media, type SV and SVK, acting as carrier for the respective polishing paste ▶ Rösler dry polishing paste, type RPP 7.. and RSP 7..

You can choose from our broad machinery range for the optimal surface finishing of your individual work pieces:

Rotary vibrators | Tub vibrators | Linear continuous flow installations | Rotomatic |
 Long Radius | High energy disc systems | Drag Finishers |
 Plunge grinding machines | Surf-Finisher | Multi-Surf-Finisher |
 Drying systems | Process water cleaning & recycling systems

For downloading
all catalogues:



MEDIA AND COMPOUNDS – ALL MADE IN-HOUSE

The worldwide most comprehensive product range



Compound production with state-of-the-art equipment

During the production of our compounds we leave nothing to chance. Our entire focus is on maintaining the highest quality. Our computer-controlled production equipment is precisely mixing the respective raw materials in fully automatic

or semi-automatic mode. And the finished products are subject to stringent quality control procedures. Subsequently, specially designed filling stations transfer the compounds into suitable transport containers, which are suitably labeled.

Production of ceramic media

The approved raw materials undergo a comprehensive conditioning process. The resulting mix is automatically shaped and then sintered at high temperatures in a continuous firing process. The ultra-modern control systems in our kilns guarantee a precise temperature curve during the entire firing operation. This is an indispensable precondition for consistent high product qualities and a guarantee for our customers to always achieve the required finishing results. For more than 80 years we have developed and produced high-quality grinding and polishing media for mass finishing applications. Rösler media ensure not only that all work pieces are optimally finished but also that the required quality is maintained, and the costs are tightly controlled.



Production of plastic media

The entire manufacturing operation, from mixing the raw materials to shaping and curing, runs fully automatically. The entire process is computer-controlled and continuously monitored. In contrast to our competitors we are adding an important step to our production process: After they have been shaped, all our plastic media undergo a tempering

operation that follows a precise temperature curve. This crucial step significantly improves the overall quality of our plastic media and is a guarantee for consistent wear characteristics and excellent grinding performance. This ensures repeatable, high-quality surface finishing results.



The non-foaming plastic media version, type “N”

The use of plastic media occasionally causes unwanted foaming, which can adversely affect the grinding performance. With our newly developed non-foaming “N” version – offered for all our standard plastic media recipes – we have resolved this problem. The non-foaming media guarantee stable finishing processes and reduce the amount of dirt residues

on the work pieces and in the machine. This guarantees more stable finishing processes with absolutely consistent results, along with a lower consumption of valuable resources like fresh water, compounds and process water cleaners.

CERAMIC MEDIA

Ordering example:	Type RM	Dimensions 10/15	Shape S
--------------------------	-------------------	----------------------------	-------------------

Type	Spec. weight g/cm ³	Grinding performance	Grinding effect
RP	2.91		
RF	2.40		
RCP	3.60		
RM	2.49		
RPM	2.50		
RCB	2.50		
RS	2.52		

Shape	D	F	S	Z	ZS	QZ
	Triangle	Triangle with big radius	Angle cut Triangle	Cylinder	Angle cut cylinder	Quinto
Dimensions (mm)	a/b	a/b	a/b	a/b	a/b	a/b
	02/02 09/09 03/03 10/06 04/04 10/10 06/06 15/15 07/07	10/10	03/08 06/10 04/04 08/12 04/10 09/09 05/05 10/15 05/10 12/04	0.8/03 03/10 1.4/05 04/10 1.5/05 05/10 1.7/05 06/10 01/03 07/15 02/05 10/15 03/05 12/25	01/03 04/10 1.2/03 04/13 1.4/05 05/10 1.5/05 06/10 1.7/05 06/13 02/05 07/15 03/05 08/15 03/10 09/20 04/05 10/20	08/08
	03/03 10/10 04/04 13/13 05/05 15/10 06/06 15/15 08/08 20/20	06/06	10/06	03/03 04/04 06/08 10/14 12/12	03/05 06/10 08/15 10/10 15/36	
	03/03 09/09 04/04 15/15 06/06 20/20 07/07 25/25 08/08		04/13 10/15 05/12 12/12 06/06 13/13 07/07 15/18 08/08 20/08 09/09	1.7/04 08/13 02/05 10/16 03/05 12/15 04/10 18/30 07/15	1.7/05 07/13 02/05 08/10 2.5/05 09/15 03/05 10/08 04/05 10/15 04/10 12/20 05/10 13/15 06/10	10/12 14/17
	02/02 20/20 03/03 25/25 04/04 30/30 06/06 40/40 08/08 50/50 10/10 13/13 15/15	06/06 08/08 10/10 13/13 15/15 20/20	03/10 15/18 04/10 16/32 06/10 20/20 08/20 20/30 10/15 25/25 10/20 30/25 13/26 30/30 15/15 35/35	02/05 12/16 04/10 12/25 05/08 15/40 06/10 20/40 07/15 08/20 09/13 10/16	1.5/06 09/20 02/05 10/15 03/05 10/20 03/10 12/20 04/10 12/25 05/10 15/25 06/13 15/30 07/15 20/20 08/15 25/30	15/15 15/18
	04/04 06/06 10/10 15/15 20/20 25/25	20/20	03/10 13/13 04/10 15/15 05/10 20/20 06/06 25/25 08/20 30/25 10/15 35/35	04/08 10/20 20/40	04/10 15/30 05/10 20/40 06/13 25/30 09/20 10/20 12/20	08/08
	04/04 15/15 05/05 20/20 06/06 25/25 08/08 30/30 10/10 40/40 13/13	10/10 15/25	04/10 13/15 06/15 15/15 07/07 20/20 10/10 25/25 10/15 30/30	06/13 10/20 15/40 20/40	03/10 10/20 15/30 20/40	
	02/02 15/15 03/03 16/16 04/04 18/20 05/05 20/12 05/10 20/16 06/06 20/20 06/08 25/25 07/07 30/25 08/08 30/30 10/08 35/10 10/10 40/40 13/13 50/50 15/12	06/06 10/10 13/13 15/15 20/20 30/30	03/05 15/15 03/10 15/18 04/04 16/32 04/10 20/20 05/10 20/30 06/06 22/08 06/10 25/25 08/20 30/25 09/10 30/30 10/15 35/35 10/20 40/40 13/26	01/04 10/20 1.4/04 12/12 1.7/04 12/16 02/05 14/40 03/10 15/30 04/10 15/40 05/10 18/40 06/10 20/40 06/14 07/13 08/20	1.5/03 08/20 02/05 09/20 2.7/05 10/15 03/05 10/20 03/10 12/20 04/10 12/25 05/10 15/20 06/10 15/25 06/13 15/30 07/13 20/40 07/15 25/30	10/12 12/12 15/15 15/18 15/25 20/20 25/25

Other types are available upon request.

Other media dimensions are available upon request
 Special media types for specific applications – please contact us or our sales representatives.

DZ Tristar	DZS Angle cut Tristar	ST Star	E Ellipse	ES Angle cut Ellipse	W Elbow	P Pyramid	K Cone	R Rhombus	PA Paraboloid	G Granulate	MS Multi-Shape (patented)	
a/b	a/b	a/b	a/b/c	a/b/c	a/b	a/b	a	a/b/c	a/b	Ø	a/b/c	
04/04 05/05 06/06 08/08 10/10	02/02 SK 03/03 SK 04/04 SK 06/06 SK 08/08 SK 10/10 SK	04/08 06/06 06/10 10/12 10/10 SK	08/09/03 20/20/08 10/10/05 15/15/04 15/15/06	15/15/04 15/15/06	10/10 SK					2 3 4 5 6 8		
04/04 02/02 SK	04/04			20/20/08						3 4 6		
04/04 05/05 06/06 08/08 10/10	06/06 SK 10/10 SK	04/05	08/09/03 15/15/06 20/20/08	15/15/06 25/30/13								
03/03 04/04 06/06 10/10 15/15 20/20 30/30	06/06 SK 10/10 SK	04/04 06/06 06/10 10/12 15/06 15/18 20/20 25/25 30/12 10/12 SK	20/08 22/12 30/12 35/12 45/16	14/14/05 15/15/04 15/15/06 20/20/08 20/20/10	15/15/04 15/15/06 20/15/08 25/25/10 25/25/13	10/05 10/10 14/14 15/10 15/15 20/20 25/25	15/16 22/25 25/27 30/34 35/39 40/45 P/R 45/50 P/R 15 P/PQ	15 19 20 30 35 40 45 60	35/18/25 50/30/30	30/17 50/28	1.2 9 2 10 3 11 4 14 5 18 6 7 8	20/09/10 41/19/20
10/10 20/20	10/10 15/15 15/18 20/10	20/12 22/10 30/12 45/16	14/14/05 15/15/04 15/15/06 20/20/08 20/20/10 25/25/10 25/25/15	20/15/08 25/25/13 25/30/10	20/20 15/15 SK	15/16 22/29 25/27 30/34 35/39 40/45 P/R 45/50 P/R 15 P/PQ	19 20 25 30 45					
03/03 04/04 10/10 20/20	10/20 20/10	30/12 45/16	08/10/03 15/15/04 15/15/06 20/20/08			15/16 25/27 30/34 35/39 40/45 P/R	30 40 60					
03/03 04/04 05/05 06/06 07/07 08/08 10/10 15/15 20/20 04/04 SK 06/06 SK 10/10 SK	04/04 05/05 06/06 06/10 10/12 10/15 15/18 20/20 30/12 10/12 SK 15/15 SK	20/08 20/12 22/12 30/12 35/12 45/16	10/10/05 14/14/05 15/15/04 15/15/06 20/20/08 20/20/10 25/25/10 25/25/15	15/15/04 20/15/06 25/15/10 25/25/13 30/30/12	10/05 10/10 15/10 15/15 20/20 14/14 SK	15/16 17/20 22/25 25/27 30/34 35/39 40/45 P/R 45/50 P/R 10 P/PQ 15 P/PQ	15 19 20 25 30 35 40 60	35/18/25 50/30/30 50/40/40 50/40/30	30/17 50/28	2 3 4 5 6 7 8 11	20/09/10 41/19/20	

... Continues on next page

CERAMIC MEDIA

Ordering example:	Type RM	Dimensions 10/15	Shape S
--------------------------	-------------------	----------------------------	-------------------

Typ	Spec. weight g/cm ³	Grinding performance	Grinding effect
RSF	2.39		
RFS	2.8		
RSG	2.51		
RXF	2.63		
RX	2.60		
RMB/D1	2.55		
RXX	2.67		

Shape	D	F	S	Z	ZS	QZ
	Triangle	Triangle with big radius	Angle cut Triangle	Cylinder	Angle cut cylinder	Quinto
Dimensions (mm)	a/b	a/b	a/b	a/b	a/b	a/b
	02/02 15/10 03/03 15/15 04/04 20/12 05/05 20/20 06/06 25/25 07/07 30/20 08/08 30/30 10/06 40/40 10/10 50/50		04/10 20/30 06/10 25/25 10/06 10/15 13/26 15/10 15/18	07/08	02/05 10/15 03/05 10/20 04/05 12/20 04/10 15/25 06/13 20/20 07/15 25/30 09/15	12/12
	03/03 04/04 06/06 10/10		05/08 06/10 10/06 10/15 15/18		03/05 04/05 06/10 07/10 10/20 15/25	
	02/02 15/15 03/03 20/20 04/04 25/25 06/06 30/30 08/08 35/35 10/10 40/40 13/13	06/06 10/10 13/13 15/15	04/10 20/20 06/10 20/30 08/20 22/08 10/15 22/24 10/20 25/25 13/26 30/25 15/15 30/30 15/18 35/35	03/05 15/30 06/10 18/40 06/14 20/40 07/15 10/16 12/16	1.5/04 08/15 02/05 10/20 03/05 12/20 03/10 12/25 04/05 15/25 04/10 15/30 05/10 20/40 06/13 25/30 07/15	10/12 15/18 20/20 25/25
	04/04 13/13 06/06 15/15 07/07 20/20 08/08 25/25 10/10 30/30	10/10 13/13 20/20 25/25	04/04 15/18 06/10 25/30 08/20 30/23 10/15 30/30 13/13 35/35 15/15		1.2/03 06/13 1.7/03 07/15 02/05 10/20 03/05 12/20 04/10 15/25 05/10	10/12
	03/03 13/13 04/04 15/15 05/05 20/20 06/06 25/15 07/07 25/25 08/08 30/30 10/10	08/08 10/10 15/15	06/10 15/18 08/20 20/20 10/10 22/08 10/15 22/24 12/10 25/25 13/13 30/25 15/15	07/13 10/15	1.7/03 08/15 03/05 12/20 04/05 15/30 06/10 20/40 07/15	10/12 15/15 15/18
	04/04 20/20 06/06 25/15 08/08 25/25 10/10 30/30 13/13 40/40 15/15	08/06 13/13 15/15	04/08 15/18 06/13 20/20 10/15 25/25 13/13 30/23 15/15 30/30	02/06 07/13 07/13 08/20 10/20 20/40	02/05 08/15 03/05 10/20 04/10 12/25 05/10 15/25 06/13 20/20 07/15	12/12 15/15 15/18 20/20
	04/04 20/20 06/06 25/15 08/08 25/25 10/10 30/30 13/13 15/15	10/10 15/15 25/25	04/04 15/18 06/10 20/20 08/08 22/08 09/09 22/24 10/10 25/25 10/15 30/30 12/20 35/35 13/13 40/40 15/15	03/10 04/10 04/10 06/10 07/13 15/30 20/40	03/05 09/15 04/05 10/20 05/10 12/20 06/10 15/25 07/15 08/15	10/12 15/15 20/20

Other types are available upon request.

DZ Tristar	DZS Angle cut Tristar	ST Star	E Ellipse	ES Angle cut Ellipse	W Elbow	P Pyramid	K Cone	R Rhombus	PA Paraboloid	G Granulate	MS Multi-Shape (patented)
 a/b	 a/b	 a/b	 a/b/c	 a/b/c	 a/b	 a/b	 a	 a/b/c	 a/b	 Ø	 a/b/c
	10/12 15/18	20/12 20/08 22/12 30/12 35/12 45/16	10/12/05 15/15/06 20/20/08 25/25/10 25/25/13	15/15/06 20/20/08 25/25/10 25/30/10 30/30/12	10/10 15/10 15/15 20/12			50/30/30 50/40/30 50/40/40			
02/02 SK 03/03 SK 04/04 SK 06/06 SK											
04/04 05/05 06/06 10/10 04/04 SK 06/06 SK 10/10 SK	04/10 06/06 06/10 10/12 15/15 15/18 20/20 20/30 25/25 30/10	20/08 22/12 30/12 35/12 45/16	10/12/05 14/14/05 15/15/04 15/15/06 20/20/08	15/15/06 25/25/10 25/25/13	10/10 15/15 20/20	15/16 22/25 25/27 30/34 35/39 40/45 P/R 45/50 P/R 15 P/PQ	15 19 20 30 35 40 60	50/30/30 30/17 50/28	2 3 4 5 6 8 11 18	20/09/10 41/19/20	
06/06	04/04 04/10 06/06 10/12 15/18 15/10 SK	30/12 45/16	08/10/03 14/14/05 15/15/06	20/20/08	14/14 SK	35/39				5.5 8	
06/06 10/10	10/12 15/18		14/14/05 15/15/06 20/20/08	25/50/13		10 P/PQ 15 P/PQ					20/09/10 41/19/20
03/03 04/04 06/06 08/08 10/10	04/04 06/06 10/10 10/12 13/20 15/18 20/20 25/10 30/12	20/08 30/12 35/12	15/15/04 15/15/06 20/20/08 25/25/10	15/15/06 20/20/08	20/20	15/16 25/27 10 P/PQ 15 P/PQ		50/30/30		8	20/09/10 41/19/20
10/10	10/12 15/18 15/06 20/20 30/10	45/16	14/14/05 20/20/08	25/25/13	10/10 15/10 15/15 20/20			50/40/40			

PLASTIC MEDIA

Ordering example:	Type RKM	Dimensions 40	Shape P
--------------------------	--------------------	-------------------------	-------------------











All standard plastic media are also available in the non-foaming "N" version

Type	Spec. weight g/cm ³	Grinding performance	Grinding effect
RKF	1.51		
RKM	1.72		
RKH/4	1.97		
RKK	1.79		
RKB/W	1.78		
RKG	1.72		
RKB/WB2	1.80		
RKV	1.82		
RKS	1.85		
RKE	1.82		
RKX	1.82		

Shape	K Cone			P Pyramid		
Dimensions (mm)	8	20		6 PQ	20	50
	10	25		10	25	60
	12	30		12	30	
	15			15	40	
	18					
	10	25	60	6 PQ	25	60
	12	30	70	10	30	70
	15	35		12	40	80
	18	40		15	45	
	20	50		20	50	
	6	18		6 PQ	20	
	10	20		10		
	12	25		12		
	15	30		15		
10	25		10	25	60	
12	30		12	30		
15	40		15	40		
20	50		20	50		
10	20	40	6 PQ	20	50	
12	25	50	10	25	60	
15	30	60	12	30		
18	35	70	15	40		
6	12	20	6 PQ	20		
8	15	25	10	30		
10	18	30	12			
15			15			
12	30	60	12	30		
15	35		15	40		
20	40		20	45		
25	50		25	50		
10	20	60	10	30		
12	25		12			
15	30		15			
18	40		20			
8	20	50	10	25	60	
10	25	60	12	30	80	
12	30		15	40		
15	40		20	50		
10	20		6 PQ	20		
12	25		10	25		
15	30		12	30		
18	40		15			
10	20		6 PQ	30		
12	25		10	40		
15	30		15			
			20			

Other types, dimensions and colors are available upon request.



PA Paraboloid	PDZ Tristar Pyramid	DK Wedge	QZ Quinto	L Lense
				
 a/b	 a	 a/b	 a	 a
16 (16/10) 20 (20/11) 30 (29/17) 40 (40/23)				
16 (16/10) 40 (40/23) 20 (20/11) 50 (50/27) 30 (29/17) 60 (60/33) 35 (35/19) 70 (70/39)	20 25 30 40 60	65/25 DZ		16
16 (16/10) 20 (20/11) 30 (29/17)	20 30	10/20 12/16 15/20 20/36	20	16
20 (20/11) 60 (60/33) 30 (29/17) 40 (40/23) 50 (50/27)	20 30 40			
16 (16/10) 40 (40/23) 20 (20/11) 50 (50/27) 30 (29/17) 60 (60/33) 35 (35/19) 70 (70/39)	20 25 30 40 60	10/20		
16 (16/10) 20 (20/11) 30 (29/17)	20	10/20		16
20 (20/11) 60 (60/33) 30 (29/17) 70 (70/39) 40 (40/23) 50 (50/27)	20 30 60	10/20	20 30	16
16 (16/10) 20 (20/11) 30 (29/17)	30			
16 (16/10) 50 (50/27) 20 (20/11) 60 (60/33) 30 (29/17) 70 (70/39) 40 (40/23)	20 25 30 40 60			
16 (16/10) 20 (20/11) 30 (29/17) 40 (40/23)				
20 (20/11) 30 (29/17) 50 (50/27)				

MASS FINISHING **COMPOUNDS**, ALL MADE IN-HOUSE

Globally the largest product range

Compounds are key ingredients for all mass finishing applications. They represent the perfect combination of eco-friendly production, precision of mass finishing processes and top quality. We are continuously striving to improve our products and processes, be it in our chemical laboratories or our Customer Experience Centers. This ensures that we are always pushing further improvements of the mass finishing technology – for the benefit of our customers.

Of course, our activities also include the development of new possibilities for cleaning and recycling the process water. The complete control of raw materials and finished products per DIN EN ISO 9001 is proof of the strict quality standards in the production of our consumables. Irrespective of whether you use standard or special products, cost efficiency and environmental protection are always part of your mass finishing operation.



You can find more information here:



COMPOUNDS FOR PROCESS WATER RECYCLING SYSTEMS

Nowadays most mass finishing machines are operated in conjunction with process water cleaning and recycling systems. The compounds used for such cleaning and recycling operations combine functionality with biological stability, high uptime and high-quality finishing results, irrespective of the application. Today, compounds for recycling mode, in combination with suitable finishing equipment and flocculants are an essential part of modern mass finishing technologies.

To make a mass finishing process even more stable and sustainable, we recently developed our Long-Life Compounds.

Long-Life Compounds minimize the maintenance work for recycling systems and, in conjunction with new process water cleaning equipment, they generate cost savings of up to 60 percent. The raw materials used in the production of the Long-Life Compounds allow particularly clean sanitary finishing operations. This results in a doubling of the process water uptime, causing less machine down times and increasing overall productivity and equipment availability. Additional benefits of the Long-Life Compounds are lower disposal costs and – since no biocides or any other additives are required – easier handling of the recycling operation.

Type	ZF 110 i	ZF 113	ZF 138	ZF 311	ZF 322	ZF 322 S	Standard	Long-Life Compounds
Description	Excellent corrosion protection for all rust-sensitive ferrous metals	General cleaning compound that offers corrosion protection for all ferrous and non-ferrous metals	Cleaning compound with excellent corrosion protection for all ferrous metals	Low-foam cleaning and passivating compound with corrosion protection, particularly suitable for stampings covered with oil	Highly effective degreasing/ de-oiling compound with corrosion protection for all metals	Highly effective degreasing/ de-oiling compound with good corrosion protection for all ferrous and non-ferrous metals		
pH value 0.5 %	9.9	8.9	9.4	9.6	8.4	9.0		
Material	Mild steel	++	+	++	++	+	++	
	Stainless steel	+	+	++	+	++	++	
	Copper/Brass	•	+	•	•	+	+	
	Aluminum	•	+	•	•	++	++	
	Zinc	•	+	•	•	+	++	
	Magnesium		•			•	+	
Application	Grinding / Deburring / Edge radiusing	++	++	++	++	+	++	
	Degreasing/ De-oiling	•	+	+	++	++	++	
	Smoothing/ Brightening	++	+	•	•	+	+	
Properties	Corrosion protection	++	+	++	++	+	++	
	Cleaning	+	+	++	++	++	+	
	Degreasing	•	+	++	++	++	++	
	Brightening	•	+	++	•	++	+	
	Foaming	•	•	•	•	•	•	
	LF 110	LF 113	LF 138	-	LF 322	LF 322		

We reserve the right for technical changes.

- ++ = Excellent/high suitability
- + = Medium suitability
- = Limited suitability

COMPOUNDS FOR APPLICATIONS USING FRESH WATER

Liquid compounds are the foundation for modern mass finishing processes. They keep the process stable and, thanks to their excellent ability to remove contaminants, they keep the work pieces and media clean. They also ensure that the media

maintains its functionality – in any mass finishing operation. The Rösler program offers you the right product for your individual applications and ensures high cost-efficiency with excellent protection of the environment.

Type	FC 115	FC 120	FC 230	FC 310	FC 396	FC 410	FC 430	FC 630 AL	
Description	Excellent corrosion protection for all rust-sensitive ferrous metals	General Cleaning and polishing compound with corrosion protection	Cleaning and polishing compound for non-ferrous metals and stainless steel	Alkaline liquid compound for all metals	Highly alkaline degreasing compound for very oily work pieces	Highly acidic pickling compound	Acidic pickling and polishing compound for all non-ferrous metals and stainless steel	Polishing compound with excellent brightening effect on all metals, especially titanium	
pH value 0.5 %	8.8	7.6	7.8	10.0	11.7	1.8	2.8	7.9	
Material	Mild steel	++	+	•	++	++	+	•	•
	Stainless steel	•	+	++	++	++	+	++	++
	Copper/Brass	•	+	++	+	•	+	++	++
	Aluminum	•	+	++	++	•		++	++
	Zinc	•	+	+	+	•		+	++
	Magnesium		•	+	•				+
Application	Grinding / Deburring / Edge radiusing	++	+	+	++	++	•	•	+
	Degreasing/ De-oiling		•	•	+	++		•	•
	Smoothing/ Brightening	•	+	++	•	•	+	++	++
	Pickling				-		++	+	
	Polishing		+	++			+	++	++
	Ball burnishing		•	+			++	++	+
	Descaling/ de-rusting						++	+	
Properties	Corrosion protection	++	+	•	++	++	•		•
	Cleaning	+	+	+	++	+	+	++	+
	Degreasing		•	•	+	++		•	•
	Brightening	•	+	++	+	•	+	++	++
	Foaming	•	+	+	-	•	+	++	++

We reserve the right for technical changes.

- ++ = Excellent/high suitability
- + = Medium suitability
- = Limited suitability

POWDER COMPOUNDS

Mass finishing compounds in powder form are used for applications where other compounds produce insufficient results: The most important tasks are intensive ("shock")

degreasing, special pickling and descaling processes, improving the grinding effect of the media and general cleaning of the media.

Type	R 11	R 20 B	R 35 E	R 40	R 55	R 60	
Description	For cleaning and corrosion protection	For cleaning, corrosion protection and brightening of the work pieces	General degreasing/de-oiling compound with corrosion protection	Highly acidic powder for pickling and descaling	Grinding additive for improving the grinding effect of the media and general cleaning of the media	Polishing powder with brightening effect	
pH value 0.5 %	11.1	9.2	10.6	1.8	10.4	8.9	
Material	Mild steel	++	+	++	+	++	+
	Stainless steel	+	+	+	+	+	+
	Copper/Brass	•	+	+	+	+	++
	Aluminum	•	+	+		•	+
	Zinc	•	+	+		•	+
	Magnesium			•			
Application	Grinding / Deburring / Edge radiusing	++	+	++		++	+
	Degreasing/ De-oiling	+	+	++			
	Smoothing/ Brightening	+	+	+		•	++
	Pickling				+		
	Polishing		+				++
	Ball burnishing						+
	Descaling/ de-rusting				+		
Properties	Corrosion protection	++	+	++		•	+
	Cleaning	++	+	++		+	+
	Degreasing	+	+	++			
	Brightening	+	+	+			++
	Foaming	+	+	+	+		+

We reserve the right for technical changes.

- ++ = Excellent/high suitability
- + = Medium suitability
- = Limited suitability

We offer **special compounds for special mass finishing applications.** Contact us for further information.

GRINDING PASTES AND GRINDING POWDER

Grinding pastes increase the metal removal rate during mass finishing processes. After an in-depth analysis we precisely adapt our products to the surface condition of the respective work pieces. Whenever non-abrasive ceramic media are used, a subsequent polishing operation is possible. Depending on the product type, the grinding pastes must no longer be

pre-mixed with water but – if desired – can be automatically added into the slightly damp mass of polishing media.

If grinding additives are used in process water cleaning and recycling systems, we recommend the use of a less foaming powder version.

Type	RSP 506 S	RSP 5064 S	RSP 587	RSP 508	RSP 5086 S	Process water recycling	Automatic dosing system	Standard
Description	General grinding product	Product with excellent grinding effect	Paste with excellent grinding effect	Product with excellent grinding effect	Paste with extremely strong grinding effect			
pH value 0.5 %	ca. 9.0	ca. 9.3	ca. 9.3	ca. 9.5	ca. 9.0			
Material	Mild steel	++	++	+	+	Process water recycling	Automatic dosing system	Standard
	Stainless steel	+	+	++	++			
	Copper/Brass	+	+	+	+			
	Aluminum	•	•	•	•			
	Zinc	•	•	•	•			
Application	Grinding / Deburring / Edge radiusing	+	++	++	++			
	Smoothing/ Brightening	+	•	•	•			
Pumpable paste for recycling operations	RSP 806	RSP 8064	RSP 887	RSP 808	RSP 8086			
Standard	RSP 626	RSP 6264	RSP 6268		RSP 6286			

We reserve the right for technical changes.

- ++ = Excellent/high suitability
- + = Medium suitability
- = Limited suitability

POLISHING PASTES AND POLISHING POWDER

Polishing pastes are used for mass finishing applications requiring a perfect finish with high luster. They are the basis for our proven Keramo-Finish® process. Selection of the right paste depends on an in-depth analysis of the work piece material and surface conditions. The development of polishing powders on the basis of our polishing pastes represents a significant technical improvement. Since our powders generate

less foam, they can be used in process water recycling systems. Pastes of the type RSP/RPP 8... and 5... must no longer be pre-mixed with water. They can be directly added into the slightly damp mass of polishing media. Dosing of the paste can be automated.

Type	RPP 503	RPP 527	RPP 579	RPP 590	RPP 520	Process water recycling	Automatic dosing system	Standard
Description	Polishing paste with a slight grinding effect	Light grinding paste with polishing effect	General polishing paste	Polishing paste with good brightening effect	Polishing paste with excellent brightening effect			
pH value 0.5 %	ca. 9.2	ca. 8.6	ca. 9.0	ca. 9.0	ca. 8.7			
Material	Mild steel	++	+	++	+	Process water recycling	Automatic dosing system	Standard
	Stainless steel	+	++	++	+			
	Copper/Brass	•	+	++	++			
	Aluminum	•	•	•	•			
	Zinc	•	•	•	•			
Application	Grinding / Deburring / Edge radiusing	+	+	+	•	Process water recycling	Automatic dosing system	Standard
	Smoothing/ Brightening	+	++	++	++			
	Polishing	+	+	++	++			
Pumpable pastes for recycling operations	RPP 803	RPP 827	RPP 879	RPP 890	RPP 820			
Standard	RPP 623	RPP 627	RPP 6279	RPP 629	RPP 632 R			

We reserve the right for technical changes.

- ++ = Excellent/high suitability
- + = Medium suitability
- = Limited suitability

We offer **special compounds for special mass finishing applications.** Contact us for further information.

DRY POLISHING

In dry polishing operations specially treated granules made from corn cob or nut shells serve as carrier material for polishing additives. After a suitable smoothing operation dry

polishing processes – which can be run in any mass finishing machine – generate perfectly polished high-luster surface finishes.

Type	RSP 797	RPP 746	RPP 747	RPP 7221 A	RPP 709	RPP 722 L3
Description	Grinding paste	Polishing additive producing a high luster	Polishing additive with good brightening effect	Polishing additive with good brightening effect, suitable for precious metals	Polishing additive producing excellent luster	Polishing additive with good brightening effect
Material	Plastic	++	+	+	+	+
	Stainless steel	+	+	+	+	++
	Non-ferrous metals	++	+	+	++	++
	Aluminum	++	+	+	++	+
	Zinc	+	+	+	++	+
	Titanium	+				++
Application	Smoothing/Brightening	++	+	+	+	++
	Polishing		+	+	+	++

We reserve the right for technical changes.

++ = Excellent/high suitability

+ = Medium suitability

Additional additives for dry polishing operations:







- ▶ **Fluid 708:** This oil-based material increases the moisture and adhesion properties of all types of polishing granules, such as granulated corn cob, nut shells, plastic granules and small wooden cubes. It is used in conjunction with grinding and polishing media for stainless steel, brass, zinc, aluminum, plastic and organic materials like animal horns.
- ▶ **Fluid 771:** This fat-based material improves the bonding characteristics and smoothing performance of polishing media that have become too dry (granulated corn cob, nut shells, plastic granules and small wooden cubes). It is used in conjunction with grinding and polishing media for stainless steel, brass, zinc, aluminum, plastic and organic materials like animal horns.
- ▶ **Granulates:** Numerous granulated media have already been enhanced with different grinding and polishing additives. These granulates can be utilized directly and must not undergo a special conditioning phase during the first hours of operation. Specially formulated granulates are especially suitable for the treatment of work pieces with cutting edges.




We offer **special compounds for special mass finishing applications.**
Contact us for further information.


AUXILIARY MASS FINISHING MEDIA

Stainless steel polishing media are used for high gloss polishing and pressure deburring of ferrous and non-ferrous metals. They are available in a variety of shapes such as balls (spheres), satellites and pins.

Additional dimensions and steel qualities are available upon request

Stainless steel polishing media	Materials	Designation	Dimensions in mm			
			Ø	a/b		
Balls	1.4301 = AISI 304 1.4034 = AISI 420 1.4401 = AISI 316	RESK 2.0 RESK 2.8 RESK 3.2 RESK 3.9 RESK 4.5 RESK 5.0	Ø 2.0 Ø 2.8 Ø 3.2 Ø 3.9 Ø 4.5 Ø 5.0			
Satellites	1.4301 = AISI 304 1.4034 = AISI 420 1.4401 = AISI 316	SAT 03/05 SAT 05/07 SAT 07/10 SAT 08/12		03/05 05/07 07/10 08/12		
Stainless steel pins	1.4301 = AISI 304 1.4034 = AISI 420	RESA 01/05 RESA 01/09 RESA 1.6/07 RESA 02/05 RESA 03/03 RESA 03/09		01/05 01/09 1.6/07 02/05 03/03 03/09		

Drying and polishing media	Materials	Designation	Dimensions in mm		grain size in mm	
			Ø	a/b		
Drying granulates / Supervelat SV	Organic product for spot-free drying and surface cleaning and polishing of a wide range of work pieces. Serves as carrier material for dry polishing operations.	SV 6 SV 8 SV 12 SV 16 SV 20 SV 30 SV 40			ca. 2.0-5.0 ca. 2.0-4.0 ca. 1.6-2.0 ca. 0.8-1.6 ca. 0.6-1.0 ca. 0.4-0.7 ca. 0.2-0.4	
Crushed nut shells	Organic product for polishing and drying of a wide range of work pieces. Serves as carrier material for dry polishing operations.	SVK 6 SVK 8 SVK 16 SVK 20 SVK 30 SVK 40			ca. 2.40-4.00 ca. 1.70-2.40 ca. 1.40-1.70 ca. 0.45-1.00 ca. 0.45-0.80 ca. 0.20-0.45	
Glass beads	Alternative drying media	RGK RGK RGK	Ø 3 ± 0.2 Ø 4 ± 0.3 Ø 5 ± 0.2			

Supporting media	Function	Designation			grain size in mm	
Anti-stick balls	Prevent flat work pieces from sticking to each other	RAT 1 RAT 2			ca. 0.3-0.9 ca. 0.00-0.3	

PROCESS WATER CLEANING


Since they offer significant cost and environmental advantages, process water cleaning and recycling systems have become the preferred wastewater treatment method. The technical principle of 2-phase separation (solid phase vs. liquid phase) by centrifugal force is the basis for these state-of-the-art

process water cleaning systems. They guarantee stable finishing operations. High-performance equipment, in combination with proven process technology, can handle most mass finishing applications, even applications outside of the mass finishing field.

Process water recycling

You will achieve

- ▶ Savings in compound usage by up to 80 %
- ▶ Savings in freshwater usage by up to 95 %
(compared to conventional water treatment systems)



LIQUID PROCESS WATER CLEANERS

Liquid process water cleaning additives work over a broad pH spectrum, are easy to handle and generate a significant increase in the productivity and efficiency of your mass finishing equipment. The dosing is variable and depends on the amounts

of contaminants in the process water. We will be happy to analyze your process water in our development and analytical laboratory and determine the flocking compound that is most suitable for your recycling system.

	Type	AR 8400/1	AR 8401	AR 8403	AR 8404	AR 8405	AR 8407	Standard	Long-Life products	Process water cleaners with foam management
Application	Solids	+	+	+	+	+	++			
	Oil /Surfactants	+	•	++	•	•	+			
	Universally usable	•	•	++	+	+	++			
	Remarks	Highly cationic, organic substance	Contains nearly no chlorides	Reduces nickel content	Good flocculation characteristics (when the process water is exposed to high mechanical loads)		Quick floc formation			
	LF version	AR 8401 LF		AR 8403 LF	AR 8404 LF	AR 8405 LF	AR 8407 LF			
		<p>They maintain the properties of the standard process water cleaners but offer the following benefits:</p> <ul style="list-style-type: none"> ▶ Improved sanitary conditions of the entire system ▶ Improved recycling properties ▶ Savings in biocide use ▶ Improved equipment availability ▶ Up to 100 % longer uptimes of the process water 								
	Versions with defoaming effect			AR 8604/2	AR 8605/2	AR 8607/1				
		<p>They maintain the properties of the standard process water cleaners but offer the following benefits:</p> <ul style="list-style-type: none"> ▶ Primarily used in case of soft process water and / or foaming compounds ▶ Require no additional dosing of defoamers ▶ Allow operation with simultaneous use of plastic and ceramic media ▶ Less downtime <p>Depending on the finishing application, finishing requirements and operating conditions both versions improve the process water uptime and improve the equipment performance.</p>								

We reserve the right for technical changes.

- ++ = Excellent/high suitability
- + = Medium suitability
- = Limited suitability

PROCESS WATER CLEANERS IN POWDER FORM

Process water cleaners in powder form are effective over a broad pH spectrum. They are primarily used to reduce the metal contents in the contaminated process water. If dosed correctly, they can – after a suitable quality check – ensure that

the cleaned water can be discharged to drain. Our in-house analytical laboratory is available to analyze your process water and to determine the right product for your finishing application.

Powder products for chemical-physical wastewater treatment

Typ	AR 7038	AR 7090	AR 7234	AR 7009	Cleaned water going to drain	AR 7120	AR 7134	Process water recycling	Granulates
Description	Composite flocculants consisting of anionic and cationic polymers, inorganic salts and clay.					Composite flocculants consisting of anionic and cationic polymers, inorganic salts and clay.			
Characteristics	Wastewater containing oil	Lowering of the sulfate content	Wastewater containing high organic loads	General purpose product		General purpose product			
Highlights			Low consumption	cost-efficient		effective removal of oil and grease			
Applications	Highly contaminated wastewater	Some salt buildup	Significant salt buildup	Minor salt buildup		Some salt buildup	Minor salt buildup		
					General purpose product	for example, if wastewater contains large amounts of surfactants			

AR 7009 G AR 7120 G AR 7134 G

- ▶ Chemically identical with the respective powders
- ▶ Create minimal amounts of dust
- ▶ Easy dosing
- ▶ Dust creation reduced by 80 %
- ▶ Free-flowing granules facilitate handling
- ▶ Faster reaction
- ▶ Not affected by foaming in the dirty water tank
- ▶ Less reactive to humidity
- ▶ Up to 20 % lower dosing quantities


We reserve the right for technical changes.

RÖSLER SMART SOLUTIONS

A digital added value to meet your challenges

Now is the time to promote the **digital transformation** and develop innovative digitization solutions. Under our new brand **Rösler Smart Solutions** we have developed a comprehensive digitization product that will allow you to **make processes**

and their parameters more transparent and to define the potential for substantial cost savings. Our package creates the **potential for optimization significant reduction of the operating costs.**



Scan the QR code to get more information



Transparency of processes and costs.



Process monitoring and recording of data.



Quick correction of deviations and faults.



Intelligent operation with uptime projections.



Optimized utilization of resources and cost reduction.

Mass Finishing
Shot Blasting
AM Solutions
www.rosler.com

Germany

Rösler Oberflächentechnik GmbH
Werk Memmelsdorf
Vorstadt 1
D-96190 Untermmerzbach
Tel.: +49 9533 / 924-0
Fax: +49 9533 / 924-300
info@rosler.com

Rösler Oberflächentechnik GmbH
Werk Hausen
Hausen 1
D-96231 Bad Staffelstein
Tel.: +49 9533 / 924-0
Fax: +49 9533 / 924-300
info@rosler.com

USA

Rösler Metal Finishing USA, L.L.C.
1551 Denso Road
USA-Battle Creek
MI 49037
Tel.: +1 269 / 4413000
Fax: +1 269 / 4413001
rosler-us@rosler.com

France

Rösler France
Z.I. de la Fontaine d'Azon
CS 50513 – St. Clément
F-89105 Sens Cedex
Tel.: +33 3 / 86647979
Fax: +33 3 / 86655194
rosler-fr@rosler.com

Italy

Rösler Italiana S.r.l.
Via Elio Vittorini 10/12
I-20863 Concorezzo (MB)
Tel.: +39 039 / 611521
Fax: +39 039 / 6115232
rosler-it@rosler.com

Switzerland

Rösler Schweiz AG
Staffelbachstraße 189
Postfach 81
CH-5054 Kirchleerau
Tel.: +41 62 / 7385500
Fax: +41 62 / 7385580
rosler-ch@rosler.com

Spain

Rösler International GmbH & Co. KG
Sucursal en España
Polg. Ind. Cova Solera C/Roma, 7
E-08191 Rubí (Barcelona)
Tel.: +34 93 / 5885585
Fax: +34 93 / 5883209
rosler-es@rosler.com

Netherlands

Rösler Benelux B.V.
Reggestraat 18
NL-5347 JG Oss
Postbus 829
NL-5340 AV Oss
Tel.: +31 412 / 646600
Fax: +31 412 / 646046
rosler-nl@rosler.com

Belgium

Rösler Benelux B.V.
Avenue de Ramelot 6
Zoning Industriel
B-1480 Tubize (Saintes)
Tel.: +32 2 / 3610200
Fax: +32 2 / 3612831
rosler-be@rosler.com

Austria

Rösler Oberflächentechnik GmbH
Hetmanekgasse 15
A-1230 Wien
Tel.: +43 1 / 6985180-0
Fax: +43 1 / 6985182
rosler-at@rosler.com

Romania

Rösler Romania SRL
Str. Avram Iancu 39-43
RO-075100 Otopeni/ILFOV
Tel.: +40 21 / 352 4416
Fax: +40 21 / 352 4935
rosler-ro@rosler.com

Russia

Rösler Russland
Borovaya Str. 7, bldg. 4, office 107
111020 Moscow
Tel. / Fax: +7 495 / 247 55 80
rosler-ru@rosler.com

Great Britain

Rösler UK Ltd.
Unity Grove, School Lane
Knowsley Business Park
GB-Prescot, Merseyside L34 9GT
Tel.: +44 151 / 4820444
Fax: +44 151 / 4824400
rosler-uk@rosler.com

Brazil

Rösler Otec do Brasil LTDA
Av. Antonio Angelo Amadio, 1421
Centro Empresarial Castelo Branco
18550-000 Boituva
São Paulo - Brasil
Tel.: +55 15 / 3264-1117
Tel.: +55 15 / 3264-1112
info@rosler-otec.com.br

China

Rösler SURFACE-TECH (BEIJING) CO., LTD.
Beijing Office
Fu Hua Mansion, Office A-11-K
No. 8, Chao Yang Men North Avenue
Beijing 100027, P.R. China
Tel.: +86 10 / 6554 73 86
Fax: +86 10 / 6554 73 87
rosler-cn@rosler.com

and over 150 additional distributors
around the world



Find your contact